Care Guide for your Flooring

TE

www.kenbrock.com.au

MAINTENANCE AND CARE GUIDE

All floors require some type of regular care to maintain their beauty. With the PUR surface protection layer Kenbrock flooring is not only protected against scuffs and scratches but is easy to care for. Your Kenbrock Floor will deliver many years of satisfaction by following these simple maintenance suggestions.



REGULAR MAINTENANCE

The regular everyday maintenance will not only keep your floor clean, but can also reduce the frequency of any more extensive maintenance.

EVERYDAY



Sweep, mop or vacuum to remove dust and other loose particles from your floor



Spot clean any marks with Kenbrock Maintain in accordance with the instructions on the bottle

WEEKLY



Sweep, mop or vacuum to remove dust and other loose particles from your floor



Wash your floor with cool to lukewarm water using Kenbrock Maintain diluted in accordance with instructions on the bottle

MAINTENANCE AND CARE PRODUCTS

MAINTAIN is a biodegradeable, pH neutral detergent which leaves all surfaces clean and citrus fresh. It is suitable for use on all hard surfaces including walls, floors, benchtops, toilets and bathrooms.

REJUVENATE is a metal bonded, water based, high-speed combination floor sealer & finish that provides superior gloss, durability and dirt release for the demands of high traffic environments. Available in gloss and satin.

REMOVE contains a unique blend of water based solvents and biodegradable surfactants. Together, they create a deep, penetrating floor stripper which removes most floor sealers and finishers quickly and efficiently.



RESTORATIVE MAINTENANCE

If your floor surface becomes dulled you can refurbish the surface appearance by applying the Kenbrock Rejuvenate floor sealer as follows:

> Strip your floor using Kenbrock Remove mixed with clean warm water and applied in accordance with the instructions on the bottle and allow to dry completely

2

When the floor is dry apply a thin layer and even coat of undiluted Kenbrock Rejuvenate across the floor using an applicator or quality cotton mop with ringer bucket. Please ensure mop is slightly damp to prevent sealer soaking into the mop.

Allow to dry then apply a second coat at right angles to the first coat and allow to dry.

Wait 24 hours for the Rejuvenate to harden then dry buff.



GENERAL TIPS

- Never slide furniture or fittings over an unprotected floor and ensure flooring protectors are used under the feet of furniture and appliances.
- Keep the floor surface clear of dirt, grit, sand and other abrasive materials, which can be walked into your home, by the use of appropriate entrance matting. Aviod entrance matting that is rubber backed as it can stain your floor.
- All spillages should be removed immediately.
- DO NOT use general household cleaners on your floor unless they are specifically for vinyl floors. Avoid using washing up liquid or any cleaning agent that contains bleach.
- DO NOT use any kind of steam or heat mop.
- Window coverings should be used to protect your floor from direct sunlight. If it is not practical use window tints or film which block harmful UV rays while still letting light through.

TROUBLE SHOOTING

SCUFF MARKS

Scuff marks are caused by friction from foot traffic across the suface of the floor. Light scuff marks can be removed by spot cleaning with Kenbrock Maintain diluted in accordance with the instructions. Heavier scuff marks may require restorative maintenance as per the instructions.

SCRATCHES

Caused by excessive grit, dirt or other abrasive particles on the floor. Minor scratching may required restorative maintenance as per the instructions. Any deep scratching or gouges in the planks may result in the individual plank/s needing to be replaced.











www.kenbrock.com.au

VIC 22-24 Edison Road Dandenong South VIC 3175 T 03 9765 2222 F 03 9765 2233

QLD 2 Kingsbury Street Brendale QLD 4500 T 07 3881 1000 F 07 3881 3287

 WA-NT
 T
 1800
 674
 145
 F
 03
 9765
 2233

 TAS-SA
 T
 1800
 674
 145
 F
 03
 9765
 2233

 NSW-ACT
 T
 1300
 785
 000
 F
 07
 3881
 3287