

# Castle Oak



**100**  
**55152**



**530**  
**55236**



**720**  
**55935**



**740**  
**55960**

# Castle Oak

Striking beauty and a rustic sawcut effect: the perfect balance between elegance and attitude.

## Technical Data

<b>Type:</b>	Vinyl Plank Flooring	<b>Colours:</b>	4
<b>Dimensions:</b>	1320mm x 196mm	<b>Country of Origin:</b>	Belgium
<b>Total Product Thickness:</b>	2.5mm	<b>Finish:</b>	Matte
<b>Wear Layer:</b>	0.55mm	<b>Surface:</b>	Embossed in Register (EMB 55)
<b>Units Per Box:</b>	14	<b>Profile:</b>	Micro Bevel
<b>m<sup>2</sup> per box:</b>	3.62	<b>Coating System:</b>	Protectonite®
<b>m<sup>2</sup> per pallet:</b>	202.72	<b>Installation Method:</b>	Direct Stick

## Performance

<b>Dimensional Stability:</b>	(EN ISO 23999) ≤0.05%	<b>Smoke Value:</b>	Direct Stick: (EN ISO 9239) 130% minutes   With Underlay: (EN ISO 9239) 307% minutes
<b>Abrasion Rating:</b>	(EN 660-2) Group T	<b>Slip Resistance:</b>	(AS 4586) P2, R9
<b>Impact Sound Reduction:</b>	Please refer to Godfrey Hirst Acoustic Performance specification sheet	<b>Castor Chair:</b>	(EN ISO 4918) No Damage
<b>Light Fastness:</b>	(EN ISO 105-B02) ≥6	<b>Residual Indentation:</b>	(EN ISO 24343-1) Norm: ≤0.10mm, 0.03mm
<b>Light Reflectance Values:</b>	100 55152-57   530 55236-35   720 55935-26   740 55960-16	<b>Warranty:</b>	25 Year Moduleo Limited Residential Warranty*
<b>Flammability:</b>	(EN ISO 9239) CRF 6.4kW/m <sup>2</sup>		

## Sustainability

<b>Product Transparency:</b>	Global Green Tag, GreenRate Level A certified
<b>Accreditation:</b>	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
<b>Indoor Air Quality:</b>	Green Building Council Compliant for VOC emission rate limits



European Made



Global Green Tag




ISO 9001 Quality Management System



ISO 14001 Environment Management System



0.55mm Wear Layer



Micro Bevel Edge



Matte Finish



25 Year Moduleo Limited Residential Warranty\*



Affordable