

Technical Data Sheet



		Standard	Result		
·	Size	ISO 24342	1220.0 mm x 180.0 mm		
· _	Thickness	ISO 24346	5.5 mm		
-X	Wear layer	ISO 24340	0.5 mm		
	Locking system ¹		5G® Fold Down installation system		
	Surface treatment		K-Guard+ PU coating		
	Warranty ²	Commercial	15 years wear		
		Domestic	Lifetime wear		
	Bevelled edge		Micro		
	Standards	EN 16511	Pass: Multilayer modular floorcovering panels		
	Classification	ISO 10874 - Commercial	33: Commercial heavy23: Domestic heavy		
		ISO 10874 - Domestic			
B ₂ -21	Reaction to fire	EN ISO 9239.1:2010	CRF: 10.4 kW/m ²		
			Smoke value: 67% min.		
	Staining	EN 438-2	Pass (grade 5)		
	Light fastness	EN ISO 105-B02	Pass (≥ 6)		
	Abrasion resistance	EN 13329 Annex E	Pass (> 4000 cycles)		
	Furniture chair leg	EN 424	Pass (no visible damage)		
	Dimensional stability	BS EN ISO 23999	Pass (≤ 0.25%)		
	Swelling	ISO 24336	Pass (0.2%)		
<u></u>	Acoustic impact noise reduction	EN ISO 10140-1:2016	ΔL _w = 21 dB		
		NCC F5.3(a) requirement of \leq 62 dB under ISO 717.2:2013	Ln,w = 56 dB		
		G6.3.2 impact insulation class ≥ 55 IIC	Pass		
		ASTM E492-09	66 dB IIC		
			Suitable for use on upper floors of residential high rise apartment buildings without the need for a separate acoustic underlay		
Ģ	Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)		
	Impact resistance	EN 13329 Annex F	Pass (≥ 1800 mm)		
	Castor chair continuous use	EN 425/ISO 4918	Pass (25,000 cycles)		
	Thermal resistance	ISO 8302	0.0515 m ² K/W		
			Suitable for underfloor heating. Max 27°C		
36	Slip resistance ³	AS4586:2013 Appendix D	R10		
8	Adhesive		None required; please install according to our installation instructions.		
Environmental Floorscore SCS-EC10.3-2014 v4.0		Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.		
	Recycling		Suitable		
8	Phthalate free		Yes		

 ^{1 5}G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

 For more information:
 Australia
 New Zealand

 Call: 1800 33 11 70
 Call: 0800 44 21 01

Email: customerservice@karndean.com.au Email: customerservice@karndean.co.nz

Visit: www.karndean.com Visit: www.karndean.com









1

² Subject to terms. Please see our website.

¹ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.





	Product Code	Size		Box Quantity		Slip Resistance
Product Code		mm	inches	m²	Pieces	Oil-Wet Ramp
	SCB-VGW81T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW82T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW84T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW85T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW86T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW89T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW103T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW107T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW110T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
Wood Designs	SCB-VGW111T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW112T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW127T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW128T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW129T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW130T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW131T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW132T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW133T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW134T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10
	SCB-VGW135T	1220.0 x 180.0	48.03" x 7.09"	2.196	10 Planks	R10