

DESSO Tactile Craft 3

8 colours

Combinable with Tactile
Craft 1 and Tactile Craft 2

100% recyclable

Standard with EcoBase®

Cradle-to-Cradle® Silver

WWW.TARKETT.COM.AU



TECHNICAL DATA SHEET

Product Characteristics	Standards	DESSO Tactile Craft 3
Type of manufacture	ISO 2424	Tufted 1/10*
Aspect	ISO 2424	Structured loop pile
Dye method		Solution dyed
Dimension	EN ISO 24342	50 x 50cm (20 tiles per box)19.68" x 19.68"
Primary backing	ISO 2424	Polyester fleece
Secondary backing	ISO 2424	DESSO EcoBase® * - 100% recyclable, contains upto 91% recycled bio-based content.*
Pile fibre composition	ISO 2424	BCF Polyamide 6 ECONYL®**
Total thickness	ISO 1765	6.0mm0.2"
Effective pile thickness	ISO 1766	3.2mm0.13"
Total mass	ISO 8543	4050g/m²119.5 oz/yd²
Total pile mass	ISO 2424	710g/m²21.0 oz/yd²
Effective pile mass	ISO 8543	490g/m²14.5 oz/yd²
Pile density	ISO 8543	0.153g/cm³0.0055 lb/in³
Number of tufts	ISO 1763	1580/dm²132104/yd²
Performance Characteristics	Standards	DESSO Tactile Craft 3
Reaction to fire	ISO AS 9239-1	Critical Radiant Flux 6.9kW/m² Smoke - 138%.min
Stroll test	ISO 6356	≤ 2.0 kV
Vertical resistance	ISO 10965	≤ 1 x 10⁹ Ohm
Horizontal resistance	ISO 10965	- Ohm
Luxury rating	EN 1307	LC 2
Dimensional stability	EN 986	≤ 0.2 %
Impact sound reduction	ISO 10140	ΔL _w 22 dB
Sound absorption	ISO 354	Freq. Hz125250500100020004000 a _s 0.000.000.050.150.300.35
Noise reduction	ISO 354	0.15 a _w
Thermal resistance	ISO 8302	≤ 0.067 m²K/W
ACCS Grading		CEHD 4* Stairs
Sustainability Performances	Standards	DESSO Tactile Craft 3
Carpet Institute Australia		ECS 4
Cradle-to-Cradle®	-	Silver
CRI Green Label Plus Certification	-	GLP 3372
Global Green Tag	-	Level A
Phthalate - free	-	Yes
Recycled Content	-	67%
Carbon Footprint	-	4.13kg CO ₂ eq/m² (Cradle-to-Gate only) 0.90kg CO ₂ eq/m² (Cradle-to-Grave only)
Material Health Statement	-	Available
Total VOC Emissions (after 28 days)	EN 16516	Gold (≤ 100 µg / m³)
ReStart® Ready		Yes
GUI Allergy Certificate #		Certificate FST 100-051-08

* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.1. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com
** ECONYL® is made from 100% regenerated content.
For products with acoustic backing: SoundMaster/SoundMaster Lite backings contain 80% recycled polyester felt, SoundMaster Thrive is a low antimony polyester felt.

DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com.au

Disclaimer: Please note that products in photos are installed for creative purposes and not according to technical specifications. Please refer to Tarkett installation instructions for guidance.



EN 14041
0493-CPR-0002

Manufactured by:

Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk





For Global Green Tag certificates please see the Tarkett Australia page at globalgreentag.com



ENDLESS POSSIBILITIES



GREEN URBAN TACTILE



BREEAM



CRI PLUS



Blue Angel



Quality- and Environmental Management System Certification
ISO 9001 & ISO 14001



cradle to cradle

Tarkett Australia
Suite 1, Level 3, 3 Columbia Court, Baulkham Hills, NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au

