

Auburn Ridge



Construction	Tufted Plaid Textured Loop Pile Carpet
Yarn	100% Wool
Yarn Specification	Multi-ply twisted, stock dyed
Width	3.66m
Standard Roll Length	35m
Yarn Weight	1084g/m ² / 32oz/yd ²
Total Weight	2756g/m ²
Pile Height	8.5mm
Total Thickness	11.5mm
Machine Gauge	1/4"
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Jute
Fire Rating	CRF 4.2kW/m ² (AS ISO 9239.1)
Insect Resistance	Protected against attack by moths (WNZ TM25)
Electrical Properties	Antistatic
Indoor Air Quality	Low Emitting VOC's
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential Light Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_