

# Settlers Peak



|                       |                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------|
| Construction          | Tufted Level Loop Pile Carpet                                                              |
| Yarn                  | 100% Wool                                                                                  |
| Yarn Specification    | Multi-ply twisted, stock dyed                                                              |
| Width                 | 3.66m                                                                                      |
| Standard Roll Length  | 35m                                                                                        |
| Yarn Weight           | 1084g/m <sup>2</sup> / 32oz/yd <sup>2</sup>                                                |
| Total Weight          | 2756g/m <sup>2</sup>                                                                       |
| Pile Height           | 8.5mm                                                                                      |
| Total Thickness       | 11.5mm                                                                                     |
| Machine Gauge         | 1/4"                                                                                       |
| Primary Backing       | Woven Polypropylene                                                                        |
| Secondary Backing     | Woven Jute                                                                                 |
| Fire Rating           | CRF 5.3kW/m <sup>2</sup> (AS ISO 9239.1)                                                   |
| Insect Resistance     | Protected against attack by moths (WNZ TM25)                                               |
| Electrical Properties | Antistatic                                                                                 |
| Indoor Air Quality    | Low Emitting VOC's                                                                         |
| Underfloor Heating    | Suitable                                                                                   |
| Rating                | Extra Heavy Duty Residential<br>Light Duty Commercial                                      |
| Stair Rating          | Suitable                                                                                   |
| Warranties            | 15 Year Residential Warranty<br>5 Year Commercial Warranty                                 |
| Installation          | All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on +61 7 5415 1134 or [belgotex.com.au](http://belgotex.com.au)
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

A world of  
perfect choices\_